

DLPX-PF DRUM ALARM - SPECIFICATIONS

OVERALL

Ingress	IP65 and NEMA4X.
Depth adjustment.....	Thumbscrew
Temperature rating.....	Polypropylene max. 90°C [200°F]
Feed pipe connection	1/2" NPT elbow
Tubing Fittings	1/4" to 3/4" inch NPT (specified each order)
Weight.....	895 g [2 lb-0 oz]
Max. depth in drum	34 inches

COMPONENTS

LED

Material	polycarbonate lens
Electrical	20 mA when flashing

Buzzer

SPL (Volume).....	103dB@2 ft.
Materials	PPE housing, SS diaphragm
Electrical	20 mA when alarming

Enclosure

Body	electrical grade PVC
Gasket	solid PVC elastomer
Screws.....	316 stainless steel
Pushbutton	Anodized aluminum bezel

Threaded Drum Plug

Material.....	polyethylene
Dimension.....	ø 50 mm
Thread	2" NPS or 63 mm Butress
Thumbscrew	Phenolic head, M8 x 1.25 mm 316SS thread

Pipe

Pipe	3/4" schedule 80 polypropylene
Foot screen.....	polypropylene mesh, 14 x 14 mesh
Float switch.....	polypropylene.

Battery

Chemistry	Lithium Manganese dioxide
Capacity:	shelf life 10years, 1200mA-hr



Oct 16, 2026